

Approved For Release 2002/06/25 : CIA-RDP89B00569R000800200001-4

ROUTING

DATE 0348Z 13 APR 64

S E C R E T

TO DIRECTOR

25X1A

FROM [redacted]

ACTION:

OGPS 1-8

INFO :

TDR: 0539Z 14 APR 64

1	10
2	11
3	12
4	13
5	14
6	15
7	16

ROUTINE

TM 73160

CITE [redacted]

192

25X1A

25X1A

25X1A

A. S184A

B. B/16 12/8, 46 [redacted]

C. HTA-3B/D-19/1°40"/78 DEGREES

D. 2.00 2104/1.98 1.98

E. 8402/232-18-27-7-5-3L 232-7-3-5-3R

F. (1) COLD AND MOIST

(2) GOOD

(3) GOOD

(4) GOOD

(5) GOOD

(6) GOOD

(7) OPERATING

G. REMARKS: TAKE RECEIVED 12/2035Z APR IN SEALED, COVERED METAL CONTAINERS. PROCESSED TRACKER FROM S164A RECEIVED IN GOOD CONDITION. RUN-OFF FOUND TO BE FOLDED LATITUINALLY FOUR TIMES ON L CAUSING FILM TO REVERSE WHEN REWINDING. STATIC ELECTRICITY INTERMITTENTLY ALONG

S E C R E T

GROUP 1
Excluded from automatic
downgrading and
declassification

Approved For Release 2002/06/25 : CIA-RDP89B00569R000800200001-4

25X1A

[REDACTED] IN 73160)

S E C R E T

PAGE TWO

EDGES OF BOTH SIDES. INTERMITTENT FOG ON L DATA CHAMBER EDGE MIDWAY
THROUGH TAKE AND BLEEDING OFF OF TITLING SIDE OF R FILM EDGE IN THE
FORM OF SEMI-SPHERE 1/4 INCH IN DIAMETER. SCATTERED, SMALL EMULSION
PEELS AND PINHOLES THROUGHOUT TAKE. FRAMES 0265R AND 0266R TORN IN
NIAGARA PRINTER. MANUFACTURER SPLICES 2419L, 0177R, AND 1589R.

END OF MESSAGE